



**RAMSAUER®**  
**DICHTSTOFFE**

# 506 GLÄTTMITTEL SPEZIAL (Special Smoother)

Ready for use – not to be diluted

Serves for final smoothing of all Ramsauer silicone-, polyurethane- and hybrid sealants.

---

## Characteristics

Ramsauer 506 GLÄTTMITTEL SPEZIAL modifies the surface tension of the sealants in such a way that the pasty compounds will be readily workable which cannot be achieved with water only.

Ramsauer 506 GLÄTTMITTEL SPEZIAL reacts neutrally and is suitable for any and all cross-linking systems including in particular our type 440 NATURSTEIN ("Natural Stone"). Ramsauer 506 GLÄTTMITTEL SPEZIAL does not cause any drying edges or spots on natural stone, and therefore it is highly recommended for this type of application.

---

## Processing

Shake before use. Spray small quantities of Ramsauer 506 GLÄTTMITTEL SPEZIAL onto the sealant requiring finishing touches directly from the bottle or by means of a spray bottle. Remove any excess material and smoothen the sealant surface by means of a spreader. In order to achieve neat joint edges cover edges with adhesive tape. Remove tape immediately after smoothing the sealant. Remove any sealant residues from the substrate immediately in order to avoid the formation of spots. Otherwise, the formation of spots/discolouration cannot be ruled out completely due to the specific characteristics of natural stone. In order to avoid contamination of the smoother with ingredients of the sealant it is recommended to use it only once. Avoid smoother pools on the sealant since this may cause the formation of water spots.

---

## Attention

Use fresh smoother only! Avoid silicone residues in the smoother. Not suitable for acrylic sealants on a dispersion basis. Using smoothers on highly sensitive types of natural stone may cause spots/discolouration which cannot be removed by means of conventional cleaners. In view of the wide range of possible influences and effects during processing and application we recommend to conduct project-specific processing and/or application tests in any case. Do not use the product in large quantities and do not let it dry since dry residues may affect the visual appearance of the sealant surface. In case of glass, immediately remove any excess smoother or smoother flowing down. Otherwise, streaks will remain.

---

## Storage

9 months (in a cool and dry place protected from frost)

---

## Packaging

1000ml spray bottles, 5 l cans

---

## Safety advice

Consult our current EC-safety data sheet. Our data sheets can be downloaded from our website [www.ramsauer.at](http://www.ramsauer.at) at any time.



**RAMSAUER®**  
**DICHTSTOFFE**

---

### **Liability for defects**

---

The information provided including but not limited to the proposals for processing and using our products are based on our knowledge and experience, usually at the time of going into print. The results of work may deviate from this information depending on the specific circumstances, in particular with respect to substrates, processing and environmental conditions. Therefore, neither this information nor any oral counselling shall constitute warranty or give rise to any liability on whatever legal ground for any specific result of work, unless we acted intentionally or by gross negligence. Ramsauer warrants that its products will have the technical characteristics according to the Technical Data Sheets up to their expiry date. Product users must consult the latest data sheet which is available upon request. Our current General Terms and Conditions apply which are available for download on our website [www.ramsauer.at](http://www.ramsauer.at) at any time.